



VENDED TOPLOAD WASHER AND DRYER













FEATURES: Washer

- Revenue enhancement cycle options
- High speed extract of 710 RPM
- Card, coin and/or central pay capable
- Time remaining countdown
- Lid does not lock during cycle allowing access to clothes or to add softener
- Self-adjusting leveling legs
- Automatic balancing suspension system
- Front access to vital parts for easy maintenance
- Available in Anthracite Grey



FEATURES: Dryer

- 4 drying programs
- Time remaining countdown with top-off feature
- Large door opening for easy loading and unloading
- Reversible door
- Front access to vital parts for easy maintenance
- Galvanized steel cylinder
- Nonremovable lint filter located in front for easy cleaning
- Powerful exhaust blower ensures short dry times and low operating costs
- Door opens 180 degrees for easy loading and unloading
- Electric or gas heating

ТҮРЕ		WASHER
CAPACITY	lbs	16
CYLINDER VOLUME	cu ft	3.26
MOTOR		
frequency controlled	Нр	.5
EXTRACTION SPEED	rpm	710
G-FORCE		150
ELECTRICAL CONNECTION		120 60Hz
ELECTRIC HEATING	kW	N/A
DRAIN		
pump		standard
drain valve		available
WATER CONSUMPTION per cycle	g	24.6
WF (water factor)		7.9
MEF (modified energy factor)		1.69
DIMENSIONS		
height	in	43
width	in	25 5/8
depth	in	28
net weight	lbs	190
SHIPPING DIMENSIONS		
height	in	28
width	in	30
depth	in	45
shipping weight	lbs	210
AGENCY APPROVALS		

ТҮРЕ		DRYER
CAPACITY	lbs	18
CYLINDER VOLUME	cu ft	7
ELECTRICAL CONNECTION		120-240V 60Hz
ELECTRIC HEATING	kW	5.35
GAS HEATING	BTU	25,000
MOTOR POWER	Нр	.33
DIMENSIONS		
height	in	43
width	in	26 7/8
depth	in	28
net weight	lbs	155
SHIPPING DIMENSIONS		
height	in	46
width	in	29
depth	in	33
shipping weight	lbs	165
AGENCY APPROVALS		

AY15-0019

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.



